

Kegelager 462-452A-TIMKEN - 462-452A-TIMKEN

https://www.123kogellager.nl/kogellager-behuizing/rollager/kegellager/462-452a-timken

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS

| Bearing Dimensions | | | Load Ratings | | | | | | Part Number | | |
|--------------------|---------|---------|---------------------------------------|-------------------------|---------------------------------------|-------------------------|-----------------------|-------|-------------|-----|------|
| Bore d | O.D. D | Width T | Dynamic ⁽¹⁾ C ₁ | Factor ⁽²⁾ e | Dynamic ⁽¹⁾ C ₂ | Factor ⁽²⁾ K | Static C ₀ | Inner | Outer | | |
| mm | mm | mm | N | | N | | N | | | | |
| 57.150 | 107.950 | 32.558 | 101900 | 0.34 | 1719 | 41700 | 22000 | 1.14 | 198000 | 462 | 452A |
| 2.2500 | 4.2500 | 1.2618 | 38100 | | | 9870 | 5380 | | 37200 | | |

| Bearing Dimensions | | | | | | | | | | Geometry Factors | | | Bearing Weight | |
|--------------------|---------|--------------------------|--|--------------------------------------|--|--------------------------------------|------------------------------------|-------------------------------|----------------|------------------|----------------|------|----------------|------|
| Width B | Width C | ER. Dr. α ⁽³⁾ | Max Shaft Fillet Radius R ⁽⁴⁾ | Backing Shoulder Dia. d _s | Max Housing Fillet Radius r ⁽⁵⁾ | Backing Shoulder Dia. D _s | Cage A ₁ ⁽⁶⁾ | A ₂ ⁽⁷⁾ | G ₁ | G ₂ | C ₃ | | | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | | | | kg | | |
| 28.217 | 27.890 | -3.1 | 2.3 | 63.6 | 67.8 | 3.3 | 188.8 | 83.8 | 2.1 | 1.4 | 58.6 | 17.1 | 0.0948 | 1.21 |
| 1.1542 | 1.0820 | -0.28 | 0.09 | 2.48 | 2.84 | 0.13 | 3.94 | 2.68 | 0.08 | 0.08 | | | 2.88 | |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | TIMKEN |
| N° Ean13 | 3663952317953 |
| Binnendiameter | 57.15 mm |
| Buitendiameter | 107.95 mm |
| Dikte | 32.558 mm |
| Verpakking | 1 |

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE