

Kegelager

27684A-27620-TIMKEN - 27684A-27620-TIMKEN

<https://www.123kogellager.nl/kogellager-behuizing/rollager/kegelager/27684a-27620-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS

| Bearing Dimensions | | | Load Ratings | | | | | | Part Number | |
|--------------------|---------|---------|---------------------------------------|-------------------------|---------------------------------------|-------------------------|-----------------------|--------|-------------|--|
| Bore d | O.D. D | Width T | Dynamic ⁽¹⁾ C ₁ | Factor ⁽²⁾ e | Dynamic ⁽³⁾ C ₂ | Factor ⁽⁴⁾ K | Static C ₀ | Inner | Outer | |
| mm | mm | mm | N | | N | | N | | | |
| 76.200 | 125.412 | 25.400 | 111900 | 1.44 | 26700 | 1.42 | 178000 | 27684A | 27620 | |
| 3.0000 | 4.9375 | 1.0000 | 24500 | | 6450 | | 39000 | | | |

| Bearing Dimensions | | | | | | | | | | Geometry Factors | | | Bearing Weight |
|--------------------|---------|--------------------------|---|--------------------------------------|--|--------------------------------------|------------------------------------|-------------------------------|----------------|------------------|----------------|------|----------------|
| Width B | Width C | ER. Cr. α ⁽¹⁾ | Max Shaft Fillet Radius R _{fs} | Backing Shoulder Dia. d _s | Max Housing Fillet Radius r ⁽²⁾ | Backing Shoulder Dia. D _s | Cage A ₁ ⁽³⁾ | A ₂ ⁽⁴⁾ | G ₁ | G ₂ | C ₃ | | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | | | | kg | |
| 25.400 | 19.840 | 0.5 | 0.8 | 86.0 | 0.8 | 120.0 | 1.5 | 1.7 | 98.2 | 41.0 | 0.1198 | 1.23 | |
| 1.0000 | 0.7813 | 0.02 | 0.03 | 3.31 | 3.35 | 0.08 | 4.72 | 4.53 | 0.06 | 0.07 | | 2.71 | |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | TIMKEN |
| N° Ean13 | 3663952321431 |
| Binnendiameter | 76.2 mm |
| Buitendiameter | 125.412 mm |
| Dikte | 25.4 mm |
| Verpakking | 1 |

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE