


Kegelager

EE470078X-470128-TIMKEN - EE470078X-470128-TIMKEN

<https://www.123kogellager.nl/kogellager-behuizing/rollager/kegellager/ee470078x-470128-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS



| Bearing Dimensions | | | Load Ratings | | | | | | Part Number | | |
|--------------------|---------|---------|---------------------------------------|-------------------------|---------------------------------------|--------------------------------------|-----------------------|-------|-------------|-----------|--------|
| Bore d | O.D. D | Width B | Dynamic ⁽¹⁾ C ₁ | Factor ⁽²⁾ e | Dynamic ⁽¹⁾ C ₂ | Factor ⁽²⁾ e ₂ | Static C ₃ | Inner | Outer | | |
| mm | mm | mm | N | | N | N | N | | | | |
| 177.800 | 327.025 | 90.488 | 102000 | 0.37 | 154 | 26400 | 16500 | 1.60 | 159000 | EE470078X | 470128 |
| 7.000 | 12.670 | 3.5025 | 20600 | | | 9200 | 37100 | | 35400 | | |

| Bearing Dimensions | | | | | | | | | | Geometry Factors | | | Bearing Weight | |
|--------------------|---------|--------------------------|---|---|---|---|------------------------------------|-------------------------------|----|------------------|----------------|----------------|----------------|-------|
| Width B | Width C | ER. Dr. α ⁽¹⁾ | Max Shaft Fillet Radius R ₁ ⁽¹⁾ | Backing Shoulder Dia. d _s ⁽¹⁾ | Max Housing Fillet Radius r ₁ ⁽¹⁾ | Backing Shoulder Dia. D _s ⁽¹⁾ | Cage A ₁ ⁽¹⁾ | A ₂ ⁽¹⁾ | | G ₁ | G ₂ | C ₁ | | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | | | | kg | |
| 92.075 | 63.500 | -21.8 | 0.7 | 291.0 | 217.0 | 0.4 | 306.5 | 294.0 | * | * | 914.1 | 104.7 | 0.1304 | 30.42 |
| 3.620 | 2.500 | -0.86 | 0.38 | 7.01 | 5.54 | 0.25 | 12.07 | 11.57 | * | * | | | 0.727 | |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | TIMKEN |
| N° Ean13 | 3663952326580 |
| Binnendiameter | 177.8 mm |
| Buitendiameter | 327.025 mm |
| Dikte | 90.488 mm |
| Verpakking | 1 |

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE