




## Kogellager enkele rij ZKLN1747-2Z-INA - ZKLN1747-2Z-INA

<https://www.123kogellager.nl/kogellager-behuizing/kogellager/enkele-rij/zkln1747-2z-ina>

**Axial angular contact ball bearings ZKLN1747-2Z**  
double direction, gap seats on both sides

<b>d</b>	17 mm	Tolerance: -0,005
<b>D</b>	47 mm	Tolerance: -0,010
<b>B</b>	25 mm	Tolerance: -0,20
<b><math>\alpha</math></b>	60 °	Contact angle
<b><math>D_{2max}</math></b>	37 mm	
<b><math>d_1</math></b>	30 mm	
<b><math>d_2</math></b>	23 mm	
<b><math>r_{1max}</math></b>	0,6 mm	
<b><math>r_{2max}</math></b>	0,3 mm	
<b>m</b>	0,22 kg	Mass
<b><math>C_a</math></b>	18500 N	Basic dynamic load rating, axial
<b><math>C_{0a}</math></b>	31000 N	Basic static load rating, axial
<b><math>n_{G,grease}</math></b>	6600 1/min	Limiting speed for grease lubrication
<b><math>M_{fr}</math></b>	0,12 Nm	Bearing frictional torque
<b><math>C_a</math></b>	450 N/μm	Axial rigidity
<b><math>G_a</math></b>	60 Nm/rad	Tilting rigidity
<b><math>M_{J2}</math></b>	0,132 kg x cm <sup>2</sup>	Mass moment of inertia for rotating inner ring
	2 μm	Axial runout
		The axial runout data for screw drive bearing arrangements are based on the rotating inner ring.
	ZM17	Designation of recommended INA locknut
	AM17	Designation of recommended INA locknut
		Locknuts not included in delivery.
<b><math>M_{ts}</math></b>	15 Nm	Tightening torque
		Only valid in conjunction with INA precision locknuts
	7157 N	Axial preload force

### PRODUCTKENMERKEN

Merk	INA
N° Ean13	3663952334868
Binnendiameter	17 mm
Binnendiameter	0.669" inch
Waterdicht maken	Flens aan beide zijden
Buitendiameter	47 mm
Buitendiameter	1.85" inch
Dikte	25 mm
Dikte	0.984" inch
Gewicht	220 g
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE