

Kogellager enkele rij ZKLN4075-2Z-INA - ZKLN4075-2Z-INA

<https://www.123kogellager.nl/kogellager-behuizing/kogellager/enkele-rij/zkln4075-2z-ina>

Axial angular contact ball bearings ZKLN4075-2Z
double direction, gap seats on both sides

d	40 mm	Tolerance: -0,008
D	75 mm	Tolerance: -0,01
B	34 mm	Tolerance: -0,28
	60 °	Contact angle
D_{1max}	67 mm	
d₁	58 mm	
d_{2max}	50 mm	
r_{1max}	0,6 mm	
r_{2max}	0,3 mm	
m	0,61 kg	Mass
C_a	43000 N	Basic dynamic load rating, axial
C_{0a}	50000 N	Basic static load rating, axial
n_{Grease}	5000 1/min	Limiting speed for grease lubrication
M_{fr}	0,95 Nm	Bearing frictional torque
s_a	1000 N/μm	Axial rigidity
s_t	550 N/mmrad	Tilting rigidity
M_J	2,26 kg x cm ²	Mass moment of inertia for rotating inner ring
	2,5 μm	Axial runout
		The axial runout data for screw drive bearing arrangements are based on the rotating inner ring.
	ZM40	Designation of recommended INA locknut
	AM40	Designation of recommended INA locknut
		Locknuts not included in delivery.
M_t	55 Nm	Tightening torque
		Only valid in conjunction with INA precision locknuts
	13412 N	Axial preload force

Design of adjacent construction

Design of adjacent construction

PRODUCTKENMERKEN

Merk	INA
N° Ean13	3663952334929
Binnendiameter	40 mm
Binnendiameter	1.575" inch
Waterdicht maken	Flens aan beide zijden
Buitendiameter	75 mm
Buitendiameter	2.953" inch
Dikte	34 mm
Dikte	1.339" inch
Gewicht	610 g
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE