




Kogellager enkele rij ZKLN5090-2Z-INA - ZKLN5090-2Z-INA

<https://www.123kogellager.nl/kogellager-behuizing/kogellager/enkele-rij/zkln5090-2z-ina>

Axial angular contact ball bearings ZKLN5090-2Z
double direction, gap seals on both sides

d	50 mm	Tolerance: -0.029
D	90 mm	Tolerance: -0.01
B	34 mm	Tolerance: -0.25
	60 °	Contact angle
D _{A,max}	82 mm	
d ₁	72 mm	
d _{2,max}	63 mm	
r _{1,max}	0,6 mm	
r _{2,max}	0,3 mm	
m	0,88 kg	Mass
C _a	46500 N	Basic dynamic load rating, axial
C _{0a}	18600 N	Basic static load rating, axial
n _{lim,grease}	5000 1/min	Limiting speed for grease lubrication
M _{lim}	0,65 Nm	Bearing frictional torque
M _{lim,stat}	320 Nmm	Axial rigidity
α _{lim}	1000 1/min/rad	Tilting rigidity
M ₀	0,24 kg × cm ²	Mass moment of inertia for rotating inner ring
	2,5 μm	Axial runout
		The axial runout data for screw drive bearing arrangements are based on the rotating inner ring.
ZMO		Designation of recommended INA locknut
AMO		Designation of recommended INA locknut
		Locknuts not included in delivery.
M _s	85 Nm	Tightening torque
		Only valid in conjunction with INA precision locknuts
	17009 N	Axial preload force

PRODUCTKENMERKEN

Merk	INA
N° Ean13	3663952334943
Binnendiameter	50 mm
Waterdicht maken	Flens aan beide zijden
Buitendiameter	90 mm
Dikte	34 mm
Gewicht	918 g
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE