


Kogellager enkele rij ZKLN80130-2Z-INA - ZKLN80130-2Z-INA


<https://www.123kogellager.nl/kogellager-behuizing/kogellager/enkele-rij/zkln80130-2z-ina>

Axial angular contact ball bearings ZKLN80130-2Z
double direction, gap seats on both sides



d	80 mm	Tolerance: -0.008
D	130 mm	Tolerance: -0.015
B	45 mm	Tolerance: -0.25
	60 °	Contact angle
D _{0,max}	120 mm	
d ₁	105 mm	
d ₂	102 mm	
r _{1,max}	0,6 mm	
r _{2,max}	0,6 mm	
m	2,7 kg	Mass
C ₀	91000 N	Basic dynamic load rating, axial
C _{0a}	26000 N	Basic static load rating, axial
n _{0,gre}	2700 1/min	Limiting speed for grease lubrication
M _{0,gre}	1,8 Nm	Bearing frictional torque
M _{0,oil}	3000 Nmm	Axial rigidity
C _{0a}	3000 Nm/rad	Tilting rigidity
M ₀	27,6 kg x cm ²	Mass moment of inertia for rotating inner ring
	3 μm	Axial runout
ZMAR0120		Designation of recommended INA locknut
AM80		Designation of recommended INA locknut
		Locknuts not included in delivery.
M ₀	160 Nm	Tightening torque
		Only valid in conjunction with INA precision locknuts
	20604 N	Axial preload force

Design of adjacent construction



Design of adjacent construction

PRODUCTKENMERKEN

Merk	INA
N° Ean13	3663952334981
Binnendiameter	80 mm
Waterdicht maken	Flens aan beide zijden
Buitendiameter	130 mm
Dikte	45 mm
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE