



Zich instellende kogellager 1218-K-TVH-C3-H218-FAG - 1218-K-TVH-C3-H218-FAG

<https://www.123kogellager.nl/kogellager-behuizing/kogellager/zich-instellende/1218-k-tvh-c3-h218-fag>

Self-aligning ball bearings 1218-K-TVH-C3 + H218
main dimensions to DIN 630 and DIN 5415, with tapered bore and adapter sleeve

d_{int}	80 mm
D	160 mm
B	30 mm
B_{min}	6 mm
c	18 mm
D_1	136,7 mm
D_{1max}	149 mm
D_2	120 mm
d	90 mm
d_1	112,7 mm
d_{1max}	101 mm
d_2	90 mm
l	82 mm
f_{amax}	2 mm
$H218$	Mass. adapter sleeve
m	2,48 kg Mass
m_1	1,21 kg Mass. adapter sleeve
C	57000 N Basic dynamic load rating, radial
e	0,17
Y_1	3,74
Y_2	5,79
C_{10}	23300 N Basic static load rating, radial
Y_2	3,92
n_0	4300 1/min Limiting speed
n_B	6600 1/min Reference speed
C_{10}	1300 N Fatigue limit load, radial

PRODUCTKENMERKEN

Merk	FAG
N° Ean13	3663952346298
Binnendiameter	80 mm
Buitendiameter	160 mm
Dikte	30 mm
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE