

## Naaldhulslager TAW5545-Z-IKO - TAW5545-Z-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/taw5545-z-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**



Shaft dia. mm	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g
55	<b>TAW 5545 Z</b>	250	—	—	—	—	—	—	—

  

Boundary dimensions mm				Standard mounting dimensions mm						Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(*)</sup>	Assembled inner ring
F <sub>w</sub>	D	C	f <sub>2</sub> Max.	Shaft dia. h8		Housing bore dia. H7		Housing bore dia. N7		N	N	rpm	IRT 5045-1
				Max.	Min.	Max.	Min.	Max.	Min.				
55	67	45	3.4	55.000	54.981	67.018	66.988	—	—	79 900	172 000	5 500	

Note(\*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 80% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952357379
Binnendiameter	55 mm
Buitendiameter	67 mm
Dikte	45 mm
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE