


Naaldhulslager TAW6545-Z-IKO - TAW6545-Z-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/taw6545-z-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS



Shaft dia. mm	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g
65	TAW 6545 Z	290	—	—	—	—	—	—	—

Boundary dimensions mm	Standard mounting dimensions mm						Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ^(*) rpm	Assembled inner ring				
	Shaft dia. H7	Shaft dia. H7	Housing bore dia. N7	Housing bore dia. N7	Max.	Min.								
F _w D C f ₂ Max.	65	77	45	3.4	65.000	64.981	77.018	76.988	—	—	88 300	207 000	4 000	IRT 5545

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 80% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952357508
Binnendiameter	65 mm
Binnendiameter	2.559" inch
Buitendiameter	77 mm
Buitendiameter	3.031" inch
Dikte	45 mm
Dikte	1.772" inch
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE