

Kegelager

67985-67920CD-TIMKEN - 67985-67920CD-TIMKEN

<https://www.123kogellager.nl/kogellager-behuizing/rollager/kegelager/67985-67920cd-timken>

TAPERED ROLLER BEARINGS
DOUBLE-ROW • TYPE TDO

TYPE TDO

| Bearing Dimensions | | | | Load Ratings | | | | | | | | |
|--------------------|---------|---------|---------------------------|------------------------|-------|-----------------------|------|------------------------|-----------------|-----------------------|--------|------|
| Bore d | O.D. D | Width T | Double Outer Ring Width C | Dynamic ⁽¹⁾ | | Static ⁽²⁾ | | Dynamic ⁽³⁾ | | Factor ⁽⁴⁾ | | |
| mm | mm | mm | mm | C ₁₀ | C | N ₁₀ | N | C ₉₀ | C ₅₀ | C ₁₀₀ | K | |
| 206.375 | 282.575 | 101.600 | 82.900 | 87000 | 13700 | 0.51 | 1.33 | 1.97 | 130000 | 114000 | 227000 | 1.15 |
| 8.1200 | 11.1200 | 4.0000 | 3.2500 | | | | | | 20300 | 25000 | 31000 | |

| Part Number | | Shaft | | | | Housing | | | | Pin | | Geometry Factors | | | Bearing Weight |
|-------------|---------|---|--------------------------------------|---|--------------------------------------|----------------|----------------|----------------|----------------|----------------|----------------|------------------|----|----|----------------|
| Inner | Outer | Max. Shaft Fillet Radius R ₁ | Backing Shoulder Dia. d ₁ | Max. Housing Fillet Radius r ₁ | Backing Shoulder Dia. D ₁ | K ₁ | K ₂ | G ₁ | G ₂ | C ₁ | C ₂ | | | | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | kg | |
| 67985 | 67920CD | 3.5 | 224.0 | 8.8 | 276.8 | 19.05 | 3.33 | 898.5 | 110.0 | 0.1380 | 17.83 | 36.87 | | | |
| | | 0.14 | 8.82 | 0.03 | 10.83 | 0.75 | 0.28 | | | | | | | | |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | TIMKEN |
| N° Ean13 | 3663952360706 |
| Binnendiameter | 206.375 mm |
| Buitendiameter | 282.575 mm |
| Dikte | 101.6 mm |
| Verpakking | 1 |

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE