

## Naaldhulslager YB2-5-4-IKO - YB2-5-4-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/yb2-5-4-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series

Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end										
3.969 (5/32)	—	—	—	YB 2.5 4	0.96	—	—	—	—	—	—	—	—

  

Boundary dimensions			Standard mounting dimensions			Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(*)</sup>	Assembled inner ring	
F <sub>w</sub>	D	C	Shaft dia. h8	Housing bore dia. J7	mm					
3.969 (5/32)	7.144 (9/32)	6.35 (250)	3.969 Max.	3.961 Min.	7.152 Max.	7.137 Min.	2 320 N	2 440 N	40 000 rpm	—

Note<sup>(\*)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952361192
Binnendiameter	3.969 mm
Binnendiameter	5/32" inch
Buitendiameter	7.144 mm
Buitendiameter	9/32" inch
Dikte	6.35 mm
Dikte	1/4" inch
Gewicht	96 g
Verpakking	1
Standaard	Geen standaard

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE