


Naaldhulslager YB64-IKO - YB64-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/yb64-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard			Mass (Ref.) g			Grease retained (Ref.) g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end	Standard	Mass (Ref.) g	Closed end	Standard	Mass (Ref.) g	Closed end		
9.525 ($\frac{3}{8}$)	—	—	—	YB 64	3.4	—	—	—	—	—	—

Boundary dimensions mm (inch)			Standard mounting dimensions mm				Basic dynamic load rating C		Basic static load rating C ₀		Allowable rotational speed ^(*) rpm	Assembled inner ring
F _w	D	C	h ₈ Min.	h ₈ Max.	J7 Min.	J7 Max.	N	N	rpm			
9.525 ($\frac{3}{8}$)	14.288 ($\frac{1}{2}$)	6.35 ($\frac{1}{4}$)	9.525	9.516	14.298	14.280	4 470	5 360	16 000	—		

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952361239
Binnendiameter	9.525 mm
Buitendiameter	14.288 mm
Dikte	6.35 mm
Gewicht	3.4 g
Verpakking	1
Standaard	Geen standaard

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE