

Naaldhulslager YB98-IKO - YB98-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/yb98-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series

Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
14.288 ($\frac{9}{16}$)	—	—	—	—	—	—	—	—	YB 98 10.1		
Boundary dimensions mm(inch)		Standard mounting dimensions mm			Basic dynamic load rating	Basic static load rating	Allowable rotational speed ^(*)	Assembled inner ring			
F_w	D	C	b_2	Shaft dia. h_8	Housing bore dia. J_7	C	C_0	Allowable rotational speed ^(*)			
14.288	19.050	12.701	500	14.288	14.277	19.062	19.041	11 600	20 400	11 000	RB 68

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952361604
Binnendiameter	14.288 mm
Binnendiameter	9/16" inch
Buitendiameter	19.05 mm
Buitendiameter	3/4" inch
Dikte	12.7 mm
Dikte	1/2" inch
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE