


Naaldhulslager BHAM1212-IKO - BHAM1212-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/bham1212-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained g	Mass (Ref.) g																										
	Standard	Mass (Ref.) g	Closed end																																				
19.050 ($\frac{3}{4}$)	—	—	—	—	—	—	—	—	—	—	—	—	—																										
<table border="1"> <thead> <tr> <th colspan="3">Boundary dimensions</th> <th colspan="3">Standard mounting dimensions</th> <th rowspan="2">Basic dynamic load rating C</th> <th rowspan="2">Basic static load rating C₀</th> <th rowspan="2">Allowable rotational speed⁽¹⁾</th> <th rowspan="2">Assembled inner ring</th> </tr> <tr> <th>F_w</th> <th>D</th> <th>C</th> <th>Shaft dia. h6 Max. Min.</th> <th>Housing bore dia. J7 Max. Min.</th> <th>mm</th> </tr> </thead> <tbody> <tr> <td>19.050 $\frac{3}{4}$</td> <td>26.988 $\frac{1}{2}$</td> <td>19.05 $\frac{7}{16}$</td> <td>1.3</td> <td>19.050 19.037</td> <td>27.000 26.979</td> <td>16 800</td> <td>22 600</td> <td>20 000</td> <td>IRB 812-1</td> </tr> </tbody> </table>														Boundary dimensions			Standard mounting dimensions			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽¹⁾	Assembled inner ring	F _w	D	C	Shaft dia. h6 Max. Min.	Housing bore dia. J7 Max. Min.	mm	19.050 $\frac{3}{4}$	26.988 $\frac{1}{2}$	19.05 $\frac{7}{16}$	1.3	19.050 19.037	27.000 26.979	16 800	22 600	20 000	IRB 812-1
Boundary dimensions			Standard mounting dimensions			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽¹⁾	Assembled inner ring																														
F _w	D	C	Shaft dia. h6 Max. Min.	Housing bore dia. J7 Max. Min.	mm																																		
19.050 $\frac{3}{4}$	26.988 $\frac{1}{2}$	19.05 $\frac{7}{16}$	1.3	19.050 19.037	27.000 26.979	16 800	22 600	20 000	IRB 812-1																														

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952361819
Binnendiameter	19.05 mm
Buitendiameter	26.988 mm
Dikte	19.05 mm
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE