

## Naaldhulslager YB124-IKO - YB124-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/yb124-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series

Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end										
19.050 ( $\frac{3}{4}$ )	—	—	—	—	—	—	—	—	—	—	—	YB 124	8.5
Boundary dimensions mm(inch)			Standard mounting dimensions mm			Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(1)</sup>	Assembled inner ring				
F <sub>w</sub>	D	C	Shaft dia. d <sub>h</sub>	Housing bore dia. J7	Basic dynamic load rating C								
19.050	25.400	6.35	19.050	19.037	25.412	25.391	7 820	10 200	8 000	—			

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952361826
Binnendiameter	19.05 mm
Buitendiameter	25.4 mm
Dikte	6.35 mm
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE