


Naaldhulslager BHAM1412-IKO - BHAM1412-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/bham1412-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



BAM BHAM

Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g																										
	Standard	Mass (Ref.) g	Closed end																																				
22.225 (7/8)	---	---	---	---	---	---	---	---	---	---	---	---	---																										
<table border="1"> <thead> <tr> <th colspan="3">Boundary dimensions</th> <th colspan="3">Standard mounting dimensions</th> <th rowspan="2">Basic dynamic load rating C</th> <th rowspan="2">Basic static load rating C₀</th> <th rowspan="2">Allowable rotational speed⁽¹⁾</th> <th rowspan="2">Assembled inner ring</th> </tr> <tr> <th>F_w</th> <th>D</th> <th>C</th> <th>Shaft dia. h6</th> <th>Housing bore dia. J7</th> <th>mm</th> </tr> </thead> <tbody> <tr> <td>22.225</td> <td>30.162</td> <td>19.05</td> <td>22.225</td> <td>30.176</td> <td>30.151</td> <td>18 000</td> <td>26 100</td> <td>18 000</td> <td>IRB 1012</td> </tr> </tbody> </table>														Boundary dimensions			Standard mounting dimensions			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽¹⁾	Assembled inner ring	F _w	D	C	Shaft dia. h6	Housing bore dia. J7	mm	22.225	30.162	19.05	22.225	30.176	30.151	18 000	26 100	18 000	IRB 1012
Boundary dimensions			Standard mounting dimensions			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽¹⁾	Assembled inner ring																														
F _w	D	C	Shaft dia. h6	Housing bore dia. J7	mm																																		
22.225	30.162	19.05	22.225	30.176	30.151	18 000	26 100	18 000	IRB 1012																														

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952361871
Binnendiameter	22.225 mm
Buitendiameter	30.162 mm
Dikte	19.05 mm
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE