

Naaldhulslager

BHAM1616-IKO - BHAM1616-IKO

https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/bham1616-iko

IKO

SHELL TYPE NEEDLE ROLLER BEARINGS

Inch Series



Identification number

Shaft dia. mm (inch)	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g
25.400 (1)	—	—	—	—	BHAM 1616	48	—	—	—	—

Boundary dimensions mm(inch)			Standard mounting dimensions mm			Basic dynamic load rating	Basic static load rating	Allowable rotational speed ⁽¹⁾	Assembled inner ring	
F_w	D	C	Shaft dia. d Max. Min.	Housing bore dia. $J7$ Max. Min.	C	C	C_0	rpm		
25.400	33.338	25.40(1.000)	25.400	25.387	33.352	33.327	26 400	44 500	15 000	IRB 1216

Notes⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.

Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952362038
Binnendiameter	25.4 mm
Buitendiameter	33.338 mm
Dikte	25.4 mm
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE