

Naaldhulslager BAM228-IKO - BAM228-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/bam228-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series

Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained g	Mass (Ref.) g
	BAM	228	29										
34.925 (1 3/8)	—	—	—	—	—	—	—	—	—	—	—	—	—

Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*) rpm	Assembled inner ring
F _w	D	C	Shaft dia. h _s Max. Min.	Housing bore dia. J ₇ Max. Min.	Max. Min.	N				
34.925 1 3/8	41.275 1 5/8	12.70 500	2.8	34.925 34.909	41.289 41.264	9 770	16 600	10 000	IRB 188	

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952363035
Binnendiameter	34.925 mm
Buitendiameter	41.275 mm
Dikte	12.7 mm
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE