


Naaldhulslager YB2416-IKO - YB2416-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/yb2416-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g				
	Standard	Mass (Ref.) g	Closed end														
38.100 (1 1/2)	—	—	—	—	—	—	—	—	—	—	—	YB 2416	105				
Boundary dimensions		mm(inch)		Standard mounting dimensions				mm		Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽¹⁾		Assembled inner ring	
F_w	D	C_1	C_2	Shaft dia. mm	Housing bore dia. mm	Max.	Min.	Max.	Min.	N	N	N	N	rpm	IRB 2016		
38.100	47.625	25.40	1.000	38.100	38.084	47.639	47.614	55	100	118	000	4	000	IRB 2016			

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952363110
Binnendiameter	38.1 mm
Buitendiameter	47.625 mm
Dikte	25.4 mm
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE