


## Naaldhulslager YB2610-IKO - YB2610-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/yb2610-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end										
41.275 (1 5/8)	—	—	—	—	—	—	—	—	—	—	—	YB 2610	69
Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(1)</sup> rpm	Assembled inner ring			
F <sub>w</sub>	D	C	Shaft dia. h8	Housing bore dia. J7	Max.	Min.					N	N	
41.275 (1 5/8)	50.800 (2)	15.88 (625)	41.275	41.259	50.818	50.788	37 000	71 700	3 500	IRB 2210			

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952363219
Binnendiameter	41.275 mm
Binnendiameter	1 5/8" inch
Buitendiameter	50.8 mm
Buitendiameter	2" inch
Dikte	15.88 mm
Dikte	5/8" inch
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE