

## Naaldhulslager BRI446828-IKO - BRI446828-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/bri446828-iko>



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)						
			$d$	$D$	$C$	$B$	$F_w$	$^{(1)} S$	
<b>69.850</b> (2 3/4)	<b>BRI 446828</b>	1 520	69.850 (2 3/4)	107.950 (4 1/2)	44.450 (1 3/4)	44.700	82.550 (3 1/4)	1.5	
Standard mounting dimensions mm			ISO cyclic loading $C$	ISO static load ring $C_0$	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring			
$d_s$	$D_s$	$f_{st \max}$	$N$	$N$					
Min.	Max.								
77	79	99.7	2	141 000	259 000	5 000	LRB 445228		

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952375465
Binnendiameter	69.85 mm
Buitendiameter	107.95 mm
Dikte	44.7 mm
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE