


Naaldhulslager GBRI61812-IKO - GBRI61812-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/gbri61812-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			<i>d</i>	<i>D</i>	<i>C</i>	<i>B</i>	<i>F_w</i>
9.525 ($\frac{3}{8}$)	GBRI 61812	74	9.525 $\frac{3}{8}$	28.575 $1\frac{1}{8}$	19.050 $\frac{3}{4}$	19.300	15.875 $\frac{5}{8}$

Standard mounting dimensions mm			Basic dynamic load C_0 N	Limiting static load rating C_0 N	Allowable rotational speed $(^{\circ})$ rpm	Assembled inner ring
d_a Min.	D_a Max.	$r_{as\ max}$ ($^{\circ}$)				
14	14.5	24.5	23 500	28 500	9 500	LRBZ 61012

Notes: ⁽¹⁾ Maximum permissible corner radius of the housing.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952377377
Binnendiameter	9.525 mm
Buitendiameter	28.575 mm
Dikte	19.3 mm
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE