


Naaldhulslager GBRI82012-IKO - GBRI82012-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/gbri82012-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F_w
12.700 (.50)	GBRI 82012	86.5	12.700 ⁽¹⁾ ₀	31.750 ⁽¹⁾ ₀	19.050 ⁽¹⁾ ₀	19.300	19.050 ⁽¹⁾ ₀
Standard mounting dimensions mm		Ball diam. mm ϕ	Ball rate mm/ring C_0	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring		
d_a Min.	d_a Max.				D_a Max.	$r_{as\ max}$ (¹)	
17.5	18	27	0.6	26 400	34 500	8 000	LRBZ 81212

Notes:⁽¹⁾ Maximum permissible corner radius of the housing.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks:
1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952377384
Binnendiameter	12.7 mm
Buitendiameter	31.75 mm
Dikte	19.05 mm
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE