


Naaldhulslager GBRI102216-IKO - GBRI102216-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/gbri102216-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F_w
15.875 (5/8)	GBRI 102216	133	15.875 ₀ ^{0.001}	34.925 ₀ ^{0.001}	25.400 ₀ ^{0.001}	25.650	22.225 ₀ ^{0.001}

Standard mounting dimensions mm			Basic dynamic load rating C_0	Limiting load rating C_0	Allowable rotational speed (1) rpm	Assembled inner ring LRBZ 101416
d_a	D_a	$r_{as max}$ (2)				
Min.	Max.	Max.	N	N		
21	21.2	30	38 300	58 300	7 000	LRBZ 101416

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952377407
Binnendiameter	15.875 mm
Binnendiameter	5/8" inch
Buitendiameter	34.925 mm
Buitendiameter	1 3/8" inch
Dikte	25.65 mm
Dikte	1.01" inch
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE