


Naaldhulslager GBRI122412-IKO - GBRI122412-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/gbri122412-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F _w
19.050 (3/4)	GBRI 122412	112	19.050 ¹⁾	38.100 ¹⁾	19.050 ¹⁾	19.300	25.400 ¹⁾
Standard mounting dimensions mm		Ball diam. mm C	Ball diam. mm C ₀	Allowable rotational speed ²⁾ rpm	Assembled inner ring		
d _s Min. Max.	D _s Max.				r _{as max} (°)		
24	24.4	33.3	0.6	31 000	46 100	6 000	LRBZ 121612

Notes: 1) Maximum permissible corner radius of the housing.
2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952377414
Binnendiameter	19.05 mm
Binnendiameter	3/4" inch
Buitendiameter	38.1 mm
Buitendiameter	1 1/2" inch
Dikte	19.3 mm
Dikte	0.76" inch
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE