


Naaldhulslager GBRI162816-IKO - GBRI162816-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/gbri162816-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F _w
25.400 (1)	GBRI 162816	184	25.400 (1)	44.450 (1) $\frac{1}{2}$	25.400 (1)	25.650	31.750 (1) $\frac{1}{2}$
Standard mounting dimensions mm		Ball diam. mm C	Ball diam. mm C ₀	Allowable rotational speed (2) rpm	Assembled inner ring		
d _s Min.	d _s Max.				D _s Max.	r _{as} max. (1)	
30.5	30.7	39.6	0.6	46 600	83 900	4 500	LRBZ 162016

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952377445
Binnendiameter	25.4 mm
Buitendiameter	44.45 mm
Dikte	25.65 mm
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE