


## Naaldhulslager GBRI223520-IKO - GBRI223520-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/gbri223520-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			<i>d</i>	<i>D</i>	<i>C</i>	<i>B</i>	<i>F<sub>w</sub></i>
<b>34.925</b> (1 1/8)	<b>GBRI 223520</b>	316	34.925 $\pm$ 0.010	55.562 $\pm$ 0.010	31.750 $\pm$ 0.010	32.000	41.275 $\pm$ 0.010

Standard mounting dimensions mm				Basic dynamic load rating <i>C</i> N	Static load rating <i>C<sub>0</sub></i> N	Allowable rotational speed (F) rpm	Assembled inner ring <b>LRBZ 222620</b>
<i>d<sub>a</sub></i> Min.	<i>d<sub>a</sub></i> Max.	<i>D<sub>a</sub></i> Max.	<i>r<sub>a</sub></i> max. (°)				
40.2	40.2	50.5	0.6	67 000	130 000	3 500	

Notes: (1) Maximum permissible corner radius of the housing.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. No grease is preapplied. Perform proper lubrication.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952377490
Binnendiameter	34.925 mm
Buitendiameter	55.562 mm
Dikte	32 mm
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE