

Naaldhulslager

GBRI243720-IKO - GBRI243720-IKO

https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/gbri243720-iko

IKO

MACHINED TYPE NEEDLE ROLLER BEARINGS

Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F _w
38.100 (1 1/2)	GBRI 243720	335	38.100 1/2	58.738 2 3/8	31.750 1 1/2	32.000	44.450 1 3/4

Standard mounting dimensions mm			Ball diameter mm C	Ball rate mm C ₀	Allowable rotational speed (2) rpm	Assembled inner ring LRBZ 242820
d _s Min.	d _s Max.	D _s Max.				
43.3	43.4	53.7	0.6	69 700	141 000	3 500

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is preapplied. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952377506
Binnendiameter	38.1 mm
Buitendiameter	58.738 mm
Dikte	32 mm
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE