


Naaldhulslager GBRI243920-IKO - GBRI243920-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/gbri243920-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F _w
38.100 (1 1/2)	GBRI 243920	410	38.100 (1 1/2)	61.912 (2 7/16)	31.750 (1 1/4)	32.000	47.625 (1 7/8)

Standard mounting dimensions mm		Ball diam. mm C	Ball rate mm C ₀	Allowable rotational speed (°) rpm	Assembled inner ring LRBZ 243020		
d _s Min. Max.	D _s Max.					r _{as max} (°)	
43.3	45	56.2	1	72 400	150 000	3 000	LRBZ 243020

Notes: (°) Maximum permissible corner radius of the housing.
(°) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952377520
Binnendiameter	38.1 mm
Binnendiameter	1 1/2" inch
Buitendiameter	61.912 mm
Buitendiameter	2 7/16" inch
Dikte	32 mm
Dikte	1.26" inch
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE