


## Naaldhulslager GBRI264120-IKO - GBRI264120-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/gbri264120-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F <sub>w</sub>
<b>41.275</b> (1 5/8)	<b>GBRI 264120</b>	435	41.275 (1) 5	65.088 (2) 5/8	31.750 (1) 1/2	32.000	50.800 (2) 1
Standard mounting dimensions mm		Basic dynamic load C <sub>10</sub> (*) N	Limiting static load C <sub>0</sub> N	Allowable rotational speed (2) rpm	Assembled inner ring		
d <sub>a</sub> Min.	d <sub>a</sub> Max.				r <sub>a</sub> max. (*)		
48	49	59.2	1	74 600	162 000	3 000	<b>LRBZ 263220</b>

Notes: (1) Maximum permissible corner radius of the housing.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. No grease is preapplied. Perform proper lubrication.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952377544
Binnendiameter	41.275 mm
Buitendiameter	65.088 mm
Dikte	32 mm
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE