


## Naaldhulslager GBR445628-IKO - GBR445628-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/gbr445628-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm ( <sup>(1)</sup> )	
			F <sub>o</sub>	D	C	D <sub>s</sub> Max.	r <sub>as</sub> max
<b>69.850</b> (2 3/4)	<b>GBR 445628</b>	690	69.850 (3 1/2)	88.900 (3 1/2)	44.450 (1 3/4)	82	1.5
Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(2)</sup>					
N	N	rpm					
147 000	336 000	2 000					

Notes:  
(1) Maximum permissible corner radius of the housing.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks:  
2. The outer ring has an oil groove and an oil hole.  
3. No grease is pre-packed. Perform proper lubrication.

## PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952377605
Binnendiameter	69.85 mm
Buitendiameter	88.9 mm
Dikte	44.45 mm
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE