


## Naaldhulslager GBR101812-IKO - GBR101812-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/gbr101812-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm ( <sup>1)</sup> )	
			F <sub>d</sub>	D	C	D <sub>s</sub> Max.	r <sub>as</sub> max
<b>15.875</b> ( <sup>5/8</sup> )	<b>GBR 101812</b>	55.5	15.875( <sup>5/8</sup> )	28.575(1 <sup>1/4</sup> )	19.050( <sup>3/4</sup> )	24.5	0.6
Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed( <sup>2)</sup> )					
N	N	rpm					
23 500	28 500	9 500					

Notes:  
<sup>1)</sup> Maximum permissible corner radius of the housing.  
<sup>2)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
 Remarks:  
 1. The outer ring has an oil groove and an oil hole.  
 2. No grease is pre-packed. Perform proper lubrication.

## PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952377698
Binnendiameter	15.875 mm
Buitendiameter	28.575 mm
Dikte	19.05 mm
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE