


## Naaldhulslager GBR223016-IKO - GBR223016-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/gbr223016-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm ( <sup>(1)</sup> )	
			F <sub>d</sub>	D	C	D <sub>s</sub> Max.	r <sub>as</sub> max
<b>34.925</b> (1 3/8)	<b>GBR 223016</b>	137	34.925( <sup>(1)</sup> / <sub>2</sub> )	47.625(1 7/8)	25.400(1)	42.8	0.6
Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(2)</sup>					
N	N	rpm					
49 500	91 800	4 500					

Notes:<sup>(1)</sup> Maximum permissible corner radius of the housing.  
<sup>(2)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks:  
1. The outer ring has an oil groove and an oil hole.  
2. No grease is preapplied. Perform proper lubrication.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952377773
Binnendiameter	34.925 mm
Buitendiameter	47.625 mm
Dikte	25.4 mm
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE