


Naaldhulslager GBR324120-IKO - GBR324120-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/gbr324120-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm ⁽¹⁾	
			F	D	C	D _s Max.	r _{as max}
50.800 (2)	GBR 324120	265	50.800 ⁽³⁾	65.088 ⁽²⁾⁽³⁾	31.750 ⁽¹⁾⁽³⁾	59.2	1
Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽⁴⁾					
N	N	rpm					
74 600	162 000	3 000					

Notes:⁽¹⁾ Maximum permissible corner radius of the housing.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks:
2. The outer ring has an oil groove and an oil hole.
3. No grease is pre-applied. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952377865
Binnendiameter	50.8 mm
Buitendiameter	65.088 mm
Dikte	31.75 mm
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE