


Naaldhulslager GBRI284824-IKO - GBRI284824-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/gbri284824-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			<i>d</i>	<i>D</i>	<i>C</i>	<i>B</i>	<i>F_w</i>
44.450 (1 1/2)	GBRI 284824	790	44.450 (1 1/2)	76.200 (3)	38.100 (1 1/2)	38.350	57.150 (2 1/4)

Standard mounting dimensions mm				Basic dynamic load (kg) <i>C</i>	Limiting static load (kg) <i>C₀</i>	Allowable rotational speed (°) rpm	Assembled inner ring
<i>d_a</i>	<i>D_a</i>	<i>r_{as max}</i> (°)	<i>r_{as max}</i>				
Min.	Max.	Max.	N	N			
52.5	55	69.2	1.5	113 000	224 000	2 500	LRBZ 283624

Notes: (°) Maximum permissible corner radius of the housing.
(°) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-applied. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952377872
Binnendiameter	44.45 mm
Buitendiameter	76.2 mm
Dikte	38.1 mm
Gewicht	514 g
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE