


Naaldhulslager GBRI284828-IKO - GBRI284828-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/gbri284828-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F _w
44.450 (1 1/2)	GBRI 284828	925	44.450 (1) 0	76.200 (3) 0	44.450 (1) 0	44.700	57.150 (2) 0

Standard mounting dimensions mm				Basic dynamic load C ₁₀ (*) N	Lubricating oil rating C ₁₀ N	Allowable rotational speed (**) rpm	Assembled inner ring LRBZ 283628
d _a Min.	d _a Max.	D _a Max.	r _{as max} (*)				
52.5	55	69.2	1.5	133 000	276 000	2 500	LRBZ 283628

Notes: (*) Maximum permissible corner radius of the housing.
(**) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-applied. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952377889
Binnendiameter	44.45 mm
Buitendiameter	76.2 mm
Dikte	44.45 mm
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE