


# Naaldhulslager GBRI325224-IKO - GBRI325224-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/gbri325224-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			<i>d</i>	<i>D</i>	<i>C</i>	<i>B</i>	<i>F<sub>w</sub></i>
<b>50.800</b> (2)	<b>GBRI 325224</b>	870	50.800 3	82.550 3 1/2	38.100 1 1/2	38.350	63.500 1 1/2

Standard mounting dimensions mm				Ball diam. mm <i>C</i>	Basic load rating <i>C<sub>0</sub></i> N	Allowable rotational speed (P) rpm	Assembled inner ring <b>LRBZ 324024</b>
<i>d<sub>s</sub></i> Min.	<i>d<sub>s</sub></i> Max.	<i>D<sub>s</sub></i> Max.	<i>r<sub>as</sub></i> max. (°)				
58	61	75.7	1.5	120 000	248 000	2 500	

Notes: (1) Maximum permissible corner radius of the housing.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. No grease is pre-packed. Perform proper lubrication.

## PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952377896
Binnendiameter	50.8 mm
Buitendiameter	82.55 mm
Dikte	38.1 mm
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE