

## Naaldhulslager RNA49-14-U-IKO - RNA49-14-U-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/rna49-14-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		$F_w$	$D$	$C$	$r_s$ (1)
<b>18</b>	---	<b>RNA 49/14U</b>	---	---	19.7	18	26	13	0.3
Standard rounding dimension $D_s$ Max. mm									
Basic dynamic load rating $C$	N	N	N	N					
Basic static load rating $C_0$	N	N	N	N					
Allowable rotational speed (1)	9 260	10 800	11 000	11 000					

Notes: (1) Minimum allowable value of chamfer dimension  $r$ .  
Allowable rotational speed applies to grease lubrication.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952378848
Binnendiameter	18 mm
Buitendiameter	26 mm
Dikte	13 mm
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE