

## Naaldhulslager RNA69-28-U-IKO - RNA69-28-U-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/rna69-28-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals	With one seal		$F_w$	$D$	$C$	$r_a$ (1)	
<b>32</b>	---	---	---	---	<b>RNA 69/28U</b>	133	32	45	30	0.3
Standard rounding dimension $D_s$ Max. mm										
	Basic dynamic load rating $C$	Basic static load rating $C_0$	Allowable rotational speed (1)							
	N	N	rpm							
	43	38 900	59 100	6 000						

Notes: (1) Minimum allowable value of chamfer dimension  $r$ .  
(2) Allowable rotational speed applies to grease lubrication.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952379074
Binnendiameter	32 mm
Buitendiameter	47 mm
Dikte	30 mm
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE