

## Naaldhulslager RNA4910-U-IKO - RNA4910-U-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/rna4910-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		$F_w$	$D$	$C$	$r_s$ (1)
58	---	<b>RNA 4910U</b>	---	---	177	58	72	22	0.6
Standard rounding dimension $D_s$ Max. mm									
	Basic dynamic load rating $C$	Basic static load rating $C_0$	Allowable rotational speed (2)						
	N	N	rpm						
68	41 300	71 100	3 500						

Notes: (1) Minimum allowable value of chamfer dimension  $r$ .  
(2) Allowable rotational speed applies to grease lubrication.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952379357
Binnendiameter	58 mm
Binnendiameter	2.283" inch
Buitendiameter	72 mm
Buitendiameter	2.835" inch
Dikte	22 mm
Dikte	0.866" inch
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE