

Naaldhulslager NA4918-UU-IKO - NA4918-UU-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/na4918-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number			Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals		With one seal	d	D	C	B
90	NA 4918UU	—	—	—	1 360	90	125	35	36

r_s mm	F_w	Standard mounting dimensions mm		Basic static load rating C_0 N	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring LRTZ 9010536		
		Min.	Max.					
1.1	105	96.5	103	118.5	106 000	238 000	1 800	LRTZ 9010536

Notes:
⁽¹⁾ Minimum allowable value of outer diameter r
⁽²⁾ Allowable rotational speed applies to grease lubrication.
 Remark:
 1. The outer ring has an oil groove and an oil hole.
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952381893
Binnendiameter	90 mm
Buitendiameter	125 mm
Dikte	36 mm
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE