

Naaldhulslager NA6918-UU-IKO - NA6918-UU-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/na6918-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number			Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals		With one seal	d	D	C	B
90	—	—	NA 6918UU	—	2 480	90	125	63	64

r _s min (1)	F _w	Standard mounting dimensions mm		Basic static load rating C ₀ N	Basic dynamic load rating C ₁₀ N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring LRTZ 9010564
		d _s Min.	d _s Max.				
1.1	105	96.5	103	118.5	172 000	471 000	1 800

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: This outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952381923
Binnendiameter	90 mm
Buitendiameter	125 mm
Dikte	64 mm
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE