

Naaldhulslager NA4928-UU-IKO - NA4928-UU-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/na4928-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
140	NA 4928UU	—	—	—	4 340	140	190	50	51

r _s min (°)	Standard mounting dimensions mm		Basic static load rating C ₀	Basic dynamic load rating C ₁₀	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring
	F _w	d _s Min. Max.				
1.5	160	148 158 182	214 000	549 000	1 200	LRTZ 14016051

Notes: (1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to grease lubrication.
Remark: This outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952382050
Binnendiameter	140 mm
Buitendiameter	190 mm
Dikte	51 mm
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE