

## Naaldhulslager NA4928-U-IKO - NA4928-U-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/na4928-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
140	—	NA 4928U	—	—	4 340	140	190	50	51

r <sub>s</sub> min <sup>(1)</sup>	F <sub>w</sub>	Standard mounting dimensions mm			Basic static load rating C <sub>0</sub> N	Basic dynamic load rating C <sub>10</sub> N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring
		d <sub>s</sub> Min.	d <sub>s</sub> Max.	D <sub>s</sub> Max.				
1.5	160	148	158	182	214 000	549 000	1 200	LRTZ 14016051

Notes: (1) Minimum allowable value of shaft diameter r.  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: This outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952382067
Binnendiameter	140 mm
Buitendiameter	190 mm
Dikte	51 mm
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE