

## Naaldhulslager BR243320-U-IKO - BR243320-U-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/br243320-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		$F_w$	$D$	$C$
<b>38.100</b> (1 1/2)		<b>BR 243320 U</b>	168	38.100 (1 1/2)	52.388 (2 1/8)	31.750 (1 1/4)
Standard mounting dimensions mm		Basic dynamic load rating $C$	Static load rating $C_0$	Allowable rotational speed <sup>(*)</sup>		
$D_4$ Max.	$r$ as max	N	N	rpm		
45.1	1.5	43 700	66 900	5 500		

Notes: (\*) Minimum allowable value of chamfer dimension  $r$   
(\*\*) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952382227
Binnendiameter	38.1 mm
Buitendiameter	52.388 mm
Dikte	31.75 mm
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE