

## Naaldhulslager BR263520-U-IKO - BR263520-U-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/br263520-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		$F_w$	$D$	$C$
<b>41.275</b> (1 5/8)		<b>BR 263520 U</b>	179	41.275 (1 5/8)	55.562 (2 3/16)	31.750 (1 1/4)
Standard mounting dimensions mm		Basic dynamic load rating $C$	Basic static load rating $C_0$	Allowable rotational speed <sup>(*)</sup>		
$D_4$ Max.	$r_{as}$ max ( <sup>(†)</sup> )	N	N	rpm		
48.3	1.5	44 800	70 900	4 500		

Notes: (\*) Minimum allowable value of chamfer dimension  $r$   
(†) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952382258
Binnendiameter	41.275 mm
Binnendiameter	1 5/8" inch
Buitendiameter	55.562 mm
Buitendiameter	2 3/16" inch
Dikte	31.75 mm
Dikte	1 1/4" inch
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE