

Naaldhulslager BRI102216-U-IKO - BRI102216-U-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/bri102216-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)			
	With two seals	With one seal		d	D	C	B
15.875 ($\frac{3}{4}$)		BRI 102216 U	113.5	15.875 ($\frac{3}{4}$)	34.925 (1 $\frac{3}{4}$)	25.400 (1)	25.650

F_w	Standard mounting dimensions (mm)			Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ^(*) rpm	Assembled inner ring LRBZ 101416 B
	Min.	Max.	Max. as max. ^(*)				
22.225 ($\frac{7}{8}$)	21	21.2	29.7	21 600	26 900	9 000	

Notes: (*) Minimum allowable value of chamfer dimension r
(**) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952382517
Binnendiameter	15.875 mm
Buitendiameter	34.925 mm
Dikte	25.4 mm
Gewicht	150 g
Verpakking	-
Standaard	Geen standaard

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE