


## Naaldhulslager BRI122416-UU-IKO - BRI122416-UU-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/bri122416-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)				
	With two seals	With one seal		d	D	C	B	
<b>19.050</b> (3/4)	<b>BRI 122416 UU</b>		<b>127</b>	19.050 (3/4)	38.100 (1 1/2)	25.400 (1)	25.650	
$F_w$	Standard mounting dimensions (mm)		Basic dynamic load rating C N	Basic static load rating $C_0$ N	Allowable rotational speed <sup>(*)</sup> rpm	Assembled inner ring		
	Min.	Max.				$d_a$	$D_a$ as max.	
25.400 (1)	24	24.4	32.9	0.6	23 600	31 300	8 000	<b>LRBZ 121616 B</b>

Notes: (\*) Minimum allowable value of diameter dimension r  
(\*\*) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952382531
Binnendiameter	19.05 mm
Buitendiameter	38.1 mm
Dikte	25.4 mm
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE