


Naaldhulslager BRI284828-UU-IKO - BRI284828-UU-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/bri284828-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



| Shaft dia. mm (inch) | Identification number | | Mass (Ref.) g | Boundary dimensions mm(inch) | | | | |
|----------------------------|-----------------------------------|---------------|-------------------------------------|---|--|----------------------|--------|----------------------|
| | With two seals | With one seal | | d | D | C | B | |
| 44.450 (1 3/4) | BRI 284828 UU | | 904 | 44.450 (1 3/4) | 76.200 (3) | 44.450 (1 3/4) | 44.700 | |
| F_w | Standard mounting dimensions (mm) | | Basic dynamic load rating C N | Basic static load rating C ₀ N | Allowable rotational speed ⁽²⁾ rpm | Assembled inner ring | | |
| | Min. | Max. | | | | Min. | Max. | |
| 57.150 (2 1/4) | 52.5 | 55 | 69.0 | 1.5 | 90 300 | 158 000 | 3 500 | LRBZ 283628 B |

Notes: (1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to grease lubrication.
Remark: This outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | IKO |
| N° Ean13 | 3663952382708 |
| Binnendiameter | 44.45 mm |
| Buitendiameter | 76.2 mm |
| Dikte | 44.45 mm |
| Verpakking | 1 |

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE